



WELDING WIRE, SCREENS & ACCESSORIES

ER70S6 CARBON STEEL WELDING WIRE

- Highest combination of manganese and silicone deoxidizers
- Permits high current welding with CO₂ gas shielding
- Can also be applied with ArCO₂
- Excellent wetting
- Good for out-of-position welding using short circuiting transfer
- Layer/level wound wire
- Certified by CWB to CSA class W48 for ER49S-6
- Certified by AWS to class A5.18 for ER70S6



Sold per spool

| Model No. | Diameter | Spool Weight | Spools Per Master Box | PROMO PRICE |
|-----------|------------------|-----------------|-----------------------|-------------|
| NT549 | 0.023" / 0.6 mm | 2 lbs. / 0.9 kg | 18 | |
| NT550 | 0.030" / 0.8 mm | 2 lbs. / 0.9 kg | 18 | |
| NT551 | 0.035" / 0.9 mm | 2 lbs. / 0.9 kg | 18 | |
| NT552 | 0.045" / 1.14 mm | 2 lbs. / 0.9 kg | 18 | |
| NT553 | 0.023" / 0.6 mm | 11 lbs. / 5 kg | 4 | |
| NT554 | 0.030" / 0.8 mm | 11 lbs. / 5 kg | 4 | |
| NT555 | 0.035" / 0.9 mm | 11 lbs. / 5 kg | 4 | |
| NT556 | 0.023" / 0.6 mm | 33 lbs. / 15 kg | 1 | |
| NT557 | 0.030" / 0.8 mm | 33 lbs. / 15 kg | 1 | |
| NT560 | 0.035" / 0.9 mm | 44 lbs. / 20 kg | 1 | |
| NT561 | 0.045" / 1.14 mm | 44 lbs. / 20 kg | 1 | |

COMBOFRAME ADJUSTABLE MODULAR WELDING SCREENS

FRAMES

- Innovative COMBOframe combines high durability with extreme versatility
- Assembles in less than 5 minutes, no tools required
- Adjustable to fit both 6-foot and 8-foot-wide welding screens
- Made with heavy-duty finished steel tubing and connects with spring-pins
- Includes 360° swivel connectors that allow various configurations



LAVASHIELD™ CURTAIN

- Specially formulated 16-mil thick vinyl
- Grommets every 12" interval
- Screen edges are hemmed with DuPont® Kevlar® stitching
- Resists to UV rays, flame and abrasion
- Sold per panel



| Model No. | Dimensions W' x H' | UV Transparency | UV Resistance | Colour | PROMO PRICE |
|--------------------------|--------------------|-----------------|---------------|--------|-------------|
| CURTAIN AND FRAME | | | | | |
| NT890 | 6 x 6 | High | Moderate | Orange | |
| NT891 | 8 x 6 | High | Moderate | Orange | |
| NT892 | 6 x 6 | Moderate | Moderate | Green | |
| NT893 | 8 x 6 | Moderate | Moderate | Green | |

AIR CARBON ARC GOUGING TORCHES

- For gouging, cutting, beveling, piercing and flushing metal
- Economical air carbon-arc cutting process
- Can be used on most metals
- Chemical changes are virtually nil, as the process is primarily physical
- Sold per pair



| Model No. | AMPS | PROMO PRICE |
|-----------|------|-------------|
| NT667 | 800 | |

AIR CARBON ARC GOUGING ELECTRODES

- Consistent copper coating DCCC
- Used for gouging out defective welds and cutting non-ferrous metals
- Electrodes are 12" in length

| Model No. | Dia." | Qty /Pkg. | PROMO PRICE |
|-----------|-------|-----------|-------------|
| NT632 | 5/32 | 100 | |
| NT633 | 3/16 | 50 | |
| NT634 | 1/4 | 50 | |
| NT635 | 5/16 | 50 | |
| NT636 | 3/8 | 50 | |
| NT637 | 1/2 | 50 | |

